



## DATA SHEET

### DEG12-55 Denka Gel Battery

#### Specifications

Nominal Voltage	12
Capacity - c20 Ah	55
Capacity - c10 Ah	49.5
Capacity - c5 Ah	42.6

#### Dimensions mm

Length	228
Width	137
Height	
Height over Terminals	213
Weight Kg	18.7

#### Terminals

Terminal type	M6
---------------	----

#### Terminal Layout

#### Performance & Characteristics

Internal Resistance Ohm	0.0056
Self Discharge	
Construction Type	Non-Spillable VRLA - valve Regulated Lead Acid Particularly suitable for cyclic applications Maintenance-free (no topping up)

#### Design Life - EUROBAT Classification

12 Year Design Life (in float applications)

#### Approvals

#### Applications

Mobility  
Solar / Photovoltaic  
golf  
Marine  
Wind Generation  
Telecommunication  
Industrial  
and many more...



Layout



Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

### CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

☎ 020 8397-1813 ☎ 020 8397-1799

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk