

DATA SHEET

NP1.2-12	Yuasa AGM Battery	
Specifications		Г
Nominal Voltage	12	_
Capacity - c20 Ah	1.2	
Capacity - c10 Ah	1.1	
Capacity - c5 Ah		
Dimensions mm		
Length	97	_
Width	48	
Height	52.5	
Height over Terminals	54.5	
Weight Kg	0.58	_
Terminals		
Terminal type	Faston 4.75	
Terminal Layout	See Layout	
Performance & Characteristics		
Internal Resistance m0hm	110.0	_
Self Discharge	3% per month at 20°C	
Construction Type	Case Material - ABS (UL.94:HB)	
	VRLA - Valve Regulated Lead Acid	
	AGM - Absorbed Glass Matt	
	Maintenance-free (no topping up)	_
Design Life - EUROBAT Classification		
	3-5 years General Purpose	
Approvals		
	ISO9001 - Quality Managemant Systems	
	. , 3	



Layout



Recyclable



Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.

All Purpose, Uninterruptable power Supply (UPS),

CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813

Applications

sales@cpcbatteries.co.uk www.cpcbatteries.co.uk