

DATA SHEET NP1.2-12FR Yuasa AGM Battery Specifications Nominal Voltage 12 Capacity - c20 Ah 1.2 Capacity - c10 Ah 1.1 Capacity - c5 Ah **Dimensions mm** 97 Length Width 48 52.5 Height **Height over Terminals** 54.5 Weight Kg 0.58 Terminals **Terminal type** Faston 4.75 Layout **Terminal Layout** See Layout Performance & Characteristics Internal Resistance m0hm 110.0 Self Discharge 3% per month at 20°C **Construction Type** Case Material - ABS (UL.94:VO) VRLA - Valve Regulated Lead Acid AGM - Absorbed Glass Matt Maintenance-free (no topping up) **Design Life - EUROBAT Classification** 3-5 years General Purpose Approvals ISO9001 - Quality Managemant Systems Recyclable Applications All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power

CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

Supply, DC Power Supply, Auto Control System.

CPC Battery Services Ltd Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA t 020 8397-1813 sales@cpcbatteries.co.uk www.cpcbatteries.co.uk