

DATA SHEET NP12-12FR Yuasa AGM Battery Specifications Nominal Voltage 12 Capacity - c20 Ah 12 Capacity - c10 Ah 11.1 Capacity - c5 Ah **Dimensions mm** YUAS Length 151 Width 98 Height 95.5 **Height over Terminals** 97.5 Weight Kg 4.05 Terminals **Terminal type** Layout Faston 6.35 **Terminal Layout** See Layout Performance & Characteristics Internal Resistance m0hm 44.4 Self Discharge Case Material - ABS (UL.94:VO) **Construction Type** VRLA - Valve Regulated Lead Acid AGM - Absorbed Glass Matt Maintenance-free (no topping up) **Design Life - EUROBAT Classification** 3-5 years General Purpose Approvals Underwriters Laboratories (UL) USA Recyclable Applications All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.

CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813

sales@cpcbatteries.co.uk www.cpcbatteries.co.uk