

DATA SHEET

NP17-12IFR	Yuasa AGM Battery
Specifications	
Nominal Voltage	12
Capacity - c20 Ah	17
Capacity - c10 Ah	15.7
Capacity - c5 Ah	
Dimensions mm	
Length	181
Width	76
Height	167
Height over Terminals	167
Weight Kg	6.1
Terminals	
Terminal type	Faston M5 F
Terminal Layout	See Layout



Layout

Performance & Characteristics

Internal Resistance m0hm 15.0

Self Discharge 3% per month at 20°C
Construction Type Case Material - ABS (UL.94:VO)
VRLA - Valve Regulated Lead Acid
AGM - Absorbed Glass Matt
Maintenance-free (no topping up)



Design Life - EUROBAT Classification

Applications

3-5 years General Purpose

Approvals

Underwriters Laboratories (UL) USA

All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic

Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.





CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813

sales@cpcbatteries.co.uk www.cpcbatteries.co.uk