



## DATA SHEET

### NP2.1-12

Yuasa AGM Battery

#### Specifications

|                   |     |
|-------------------|-----|
| Nominal Voltage   | 12  |
| Capacity - c20 Ah | 2.1 |
| Capacity - c10 Ah | 1.9 |
| Capacity - c5 Ah  |     |

#### Dimensions mm

|                       |      |
|-----------------------|------|
| Length                | 178  |
| Width                 | 34   |
| Height                | 62   |
| Height over Terminals | 64   |
| Weight Kg             | 0.82 |

#### Terminals

|                 |             |
|-----------------|-------------|
| Terminal type   | Faston 4.75 |
| Terminal Layout | See Layout  |

#### Performance & Characteristics

|                          |  |
|--------------------------|--|
| Internal Resistance mOhm | 65.0   |
| Self Discharge           | 3% per month at 20°C   |
| Construction Type        | Case Material - ABS (UL94:HB)<br>VRLA - Valve Regulated Lead Acid<br>AGM - Absorbed Glass Matt<br>Maintenance-free (no topping up) |

#### Design Life - EUROBAT Classification

3-5 years General Purpose

#### Approvals

ISO9001 - Quality Management Systems

#### Applications

All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.



#### Layout



#### Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

### CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk