

## **DATA SHEET**

NP2.3-12	Yuasa AGM Battery	
Specifications		
Nominal Voltage	12	
Capacity - c20 Ah	2.3	
Capacity - c10 Ah	2.1	
Capacity - c5 Ah		VIIASA
Dimensions mm		MON SPELLANDS
Length	178	MA Michael Pall III
Width	34	
Height	62	
Height over Terminals	64	
Weight Kg	0.95	
Terminals		
Terminal type	Faston 4.75	Layout
Terminal Layout	See Layout	
Performance & Characteristics		
Internal Resistance m0hm	65.0	
Self Discharge	3% per month at 20°C	
Construction Type	Case Material - ABS (UL.94:HB)	
	VRLA - Valve Regulated Lead Acid	<u></u>
	AGM - Absorbed Glass Matt	
	Maintenance-free (no topping up)	
Design Life - EUROBAT Classification		
	3-5 years General Purpose	
Approvals		
	ISO9001 - Quality Managemant Systems	Recyclable
Applications		
	All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup	

CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.

**CPC Battery Services Ltd** 

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813

sales@cpcbatteries.co.uk www.cpcbatteries.co.uk