



DATA SHEET

NP24-12I Yuasa AGM Battery

Specifications

Nominal Voltage	12
Capacity - c20 Ah	24
Capacity - c10 Ah	22.3
Capacity - c5 Ah	

Dimensions mm

Length	166
Width	175
Height	125
Height over Terminals	125
Weight Kg	9

Terminals

Terminal type	Faston M5 F
Terminal Layout	See Layout

Performance & Characteristics

Internal Resistance mOhm	22.2
Self Discharge	3% per month at 20°C
Construction Type	Case Material - ABS (UL94:HB) VRLA - Valve Regulated Lead Acid AGM - Absorbed Glass Matt Maintenance-free (no topping up)

Design Life - EUROBAT Classification

3-5 years General Purpose

Approvals

Underwriters Laboratories (UL) USA

Applications

All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.



Layout



Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk