

## **DATA SHEET**

NP4-12	Yuasa AGM Battery
Specifications	
Nominal Voltage	12
Capacity - c20 Ah	4
Capacity - c10 Ah	3.7
Capacity - c5 Ah	
Dimensions mm	
Length	90
Width	70
Height	104
Height over Terminals	106
Weight Kg	1.75
Terminals	
Terminal type	Faston 4.75
Terminal Layout	See Layout
Performance & Characteristics	



Layout

Performance & Characteristic

Internal Resistance m0hm 40.0

**Self Discharge** 3% per month at 20°C **Construction Type** Case Material - ABS (UL.94:HB) VRLA - Valve Regulated Lead Acid

AGM - Absorbed Glass Matt Maintenance-free (no topping up)



**Design Life - EUROBAT Classification** 

3-5 years General Purpose

**Approvals** ISO9001 - Quality Managemant Systems

**Applications** 

All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.



Recyclable

CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

**CPC Battery Services Ltd** 

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813

sales@cpcbatteries.co.uk www.cpcbatteries.co.uk