



DATA SHEET

NP4-6

Yuasa AGM Battery

Specifications

Nominal Voltage	6
Capacity - c20 Ah	4
Capacity - c10 Ah	3.7
Capacity - c5 Ah	

Dimensions mm

Length	70
Width	47
Height	103.5
Height over Terminals	105.5
Weight Kg	0.87

Terminals

Terminal type	Faston 4.75
Terminal Layout	See Layout

Performance & Characteristics

Internal Resistance mOhm	20.0
Self Discharge	3% per month at 20°C
Construction Type	Case Material - ABS (UL94:HB) VRLA - Valve Regulated Lead Acid AGM - Absorbed Glass Matt Maintenance-free (no topping up)

Design Life - EUROBAT Classification

3-5 years General Purpose

Approvals

ISO9001 - Quality Management Systems

Applications

All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.



Layout



Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk