



DATA SHEET

NP65-12I Yuasa AGM Battery

Specifications

Nominal Voltage	12
Capacity - c20 Ah	65
Capacity - c10 Ah	60.5
Capacity - c5 Ah	

Dimensions mm

Length	350
Width	166
Height	174
Height over Terminals	174
Weight Kg	23

Terminals

Terminal type	Faston M6 F
Terminal Layout	See Layout

Performance & Characteristics

Internal Resistance mOhm	10.5
Self Discharge	3% per month at 20°C
Construction Type	Case Material - ABS (UL94:HB) VRLA - Valve Regulated Lead Acid AGM - Absorbed Glass Matt Maintenance-free (no topping up)

Design Life - EUROBAT Classification

3-5 years General Purpose

Approvals

Underwriters Laboratories (UL) USA

Applications

All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.



Layout



Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813

sales@cpcbatteries.co.uk

