

DATA SHEET

NP7-12	Yuasa AGM Battery	
Specifications		
Nominal Voltage	12	
Capacity - c20 Ah	7	
Capacity - c10 Ah	6.4	NP7-12
Capacity - c5 Ah		valve regulated lend acid battery
Dimensions mm		YUASA [ead acro button]
Length	151	WWW.yuasaeur
Width	65	NON-SPILLABLE DE SIGNED FOR STANDBY USE YES No. G. 18000W
Height	95.5	Nea accounts
Height over Terminals	97.5	
Weight Kg	2.65	
Terminals		
Terminal type	Faston 4.75	Layout
Terminal Layout	See Layout	•
Performance & Characteristics		
nternal Resistance m0hm	23.0	
Self Discharge	3% per month at 20°C	│_█ ▃
Construction Type	Case Material - ABS (UL.94:HB)	
	VRLA - Valve Regulated Lead Acid	
	AGM - Absorbed Glass Matt	l
	Maintenance-free (no topping up)	
Design Life - EUROBAT Classificatio	n	
	3-5 years General Purpose	
Approvals		
	Underwriters Laboratories (UL) USA	Recyclable
Applications		
	All Purpose, Uninterruptable power Supply (UPS),	
	Electric Power System (EPS), Emergency Backup	
	Power supply, Emergency Lighting, Railway Signal,	
	. otto: sappi), Emergency Elements, named Signal,	

CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813

sales@cpcbatteries.co.uk www.cpcbatteries.co.uk