



DATA SHEET

NPL200-6FR Yuasa AGM Battery

Specifications

Nominal Voltage	6
Capacity - c20 Ah	200
Capacity - c10 Ah	176
Capacity - c5 Ah	

Dimensions mm

Length	398
Width	176
Height	250
Height over Terminals	250
Weight Kg	39

Terminals

Terminal type	M10 LUG
Terminal Layout	See Layout

Performance & Characteristics

Internal Resistance mOhm	1.3
Self Discharge	3% per month at 20°C
Construction Type	Case Material - ABS (UL94:VO) VRLA - Valve Regulated Lead Acid AGM - Absorbed Glass Matt Maintenance-free (no topping up)

Design Life - EUROBAT Classification

10 to 12 years General Purpose

Approvals

Underwriters Laboratories (UL) USA

Applications

All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.



Layout



Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

☎ 020 8397-1813

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk