



## DATA SHEET

### NPL78-12IFR Yuasa AGM Battery

#### Specifications

Nominal Voltage	12
Capacity - c20 Ah	78
Capacity - c10 Ah	72.1
Capacity - c5 Ah	

#### Dimensions mm

Length	380
Width	166
Height	174
Height over Terminals	174
Weight Kg	27.5

#### Terminals

Terminal type	M8 F
Terminal Layout	See Layout

#### Performance & Characteristics

Internal Resistance mOhm	Less than 5
Self Discharge	3% per month at 20°C
Construction Type	Case Material - ABS (UL94:VO) VRLA - Valve Regulated Lead Acid AGM - Absorbed Glass Matt Maintenance-free (no topping up)

#### Design Life - EUROBAT Classification

10 to 12 years General Purpose

#### Approvals

Underwriters Laboratories (UL) USA

#### Applications

All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.



#### Layout



#### Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

### CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

**t 020 8397-1813**

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk