



DATA SHEET

A512/115A Sonnenschein A500 Gel Battery

Specifications

Nominal Voltage	12
Capacity - c20 Ah	115
Capacity - c10 Ah	
Capacity - c5 Ah	

Dimensions mm

Length	286
Width	269
Height	208
Height over Terminals	230
Weight Kg	37.5

Terminals

Terminal type	A - Standard tapered automotive post
Terminal Layout	See Layout

Performance & characteristics

Internal Resistance mOhm	4.60
Self Discharge	
Type	Non-Spillable VRLA - valve Regulated Lead Acid Particularly suitable for cyclic applications Maintenance-free (no topping up)

Design Life - EUROBAT Classification

6-9 years General Purpose

Approvals


Underwriters Laboratories (UL) USA
DIN/Gost/TUV, Russia

Applications

All Purpose, Uninterruptable power Supply (UPS),
Electric Power System (EPS), Emergency Backup Power
supply, Emergency Lighting, railway Signal, Aircraft
Signal, Alarm and Security System, Electronic
Apparatus and Equipment, Communication Power
Supply, DC Power Supply, Auto Control System.



Layout



Recyclable



CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813 f 020 8397-1799

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk