

DATA SHEET		
DXL100 - Elite Marine Battery		
Specifications		
Nominal Voltage	12	
Capacity - c20 Ah	85	
Reserve Capacity (Minutes)	140	ALL IN THE DESCRIPTION
Cold Cranking Amps	700	
Dimensions mm		
Length	258	
Width	172	
Height	200	
Height over Terminals	221	
Weight Kg	18.86	No. 19. 1 (marganeous and a second
Terminals		
Terminal type	Dual - Round Post & M8 Threaded	Layout
Terminal Layout	See Layout	
Performance & Characteristics	, ·	
Internal Resistance m0hm		
Self Discharge		
Construction Type	Non-Spillable	
	Sealed Wet Lead Acid	
	Maintenance-free (no topping up)	
Design Life - EUROBAT Classifica	tion	
Approvals		
		Recyclable
Applications		
	Multi purpose - Light engine starting and domestic use - Ideal for Marine and Leisure appications.	

CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA t 020 8397-1813 f 020 8397-1799 sales@cpcbatteries.co.uk www.cpcbatteries.co.uk