



## DATA SHEET

### M12V155FT Exide Marathon AGM Battery

#### Specifications

Nominal Voltage	12
Capacity - c10 Ah	150
Capacity - c8 Ah	155

#### Dimensions mm

Length	559
Width	124
Height	
Height over Terminals	283
Weight Kg	53.8

#### Terminals

Terminal type

Terminal Layout

#### Performance & Characteristics

Internal Resistance mOhm 3.00

Self Discharge

Construction Type

**FRONT Terminal**

**Particularly suitable for telecommunications**

Flame Retardant to UL94 V-0

Integrated Flash Arrestor Ultrasonically welded cover

Diamond Side Wall to endure high temperatures


Non-Spillable

VRLA - valve Regulated Lead Acid

Maintenance-free (no topping up)



#### Layout



#### Design Life - EUROBAT Classification

6-9 years General Purpose

#### Approvals

Underwriters Laboratories (UL) USA

DIN/Gost/TUV, Russia

#### Applications

**Telecommunications** - Distributed Power - PCS -

Cellular - Broadband

**Electric Utility** - Switchgear Control Power -

Communications

#### Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

### CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

**t 020 8397-1813 f 020 8397-1799**

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk