



## DATA SHEET

### GF06160V1 Sonnenschein Gel Battery

#### Specifications

Nominal Voltage	6v
Capacity - c20 Ah	196
Capacity - c10 Ah	
Capacity - c5 Ah	160

#### Dimensions mm

Length	246
Width	192
Height	
Height over Terminals	275
Weight Kg	29

#### Terminals

Terminal type	A - Standard tapered automotive post
Terminal layout	See layout

#### Performance & Characteristics

Internal Resistance mOhm	
Self Discharge	
Construction Type	Non-Spillable VRLA - Valve Regulated Lead Acid Particularly suitable for cyclic applications Maintenance-free (no topping up)

#### Design Life - EUROBAT Classification

6-9 years General Purpose

#### Approvals

#### Applications

All Purpose, Uninterruptable Power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.

700 cycles according to IEC 60 254-1



#### Layout



#### Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

### CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813 f 020 8397-1799

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk