



## DATA SHEET

### GF06180VQ Sonnenschein Gel Battery

#### Specifications

Nominal Voltage	6v
Capacity - c20 Ah	200
Capacity - c10 Ah	
Capacity - c5 Ah	180

#### Dimensions mm

Length	246
Width	192
Height	
Height over Terminals	284
Weight Kg	31.5

#### Terminals

Terminal type	F-M10
Terminal layout	See layout

#### Performance & Characteristics

Internal Resistance mOhm

Self Discharge

Construction Type

Non-Spillable  
 VRLA - Valve Regulated Lead Acid  
 Particularly suitable for cyclic applications  
 Maintenance-free (no topping up)

#### Design Life - EUROBAT Classification

6-9 years General Purpose

#### Approvals

#### Applications

All Purpose, Uninterruptable Power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.

700 cycles according to IEC 60 254-1



#### Layout



#### Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

### CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813 f 020 8397-1799

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk