



DATA SHEET

GF12052YO Sonnenschein Gel Battery

Specifications

Nominal Voltage	12v
Capacity - c20 Ah	60
Capacity - c10 Ah	
Capacity - c5 Ah	52.7

Dimensions mm

Length	261
Width	170
Height	
Height over Terminals	178
Weight Kg	19.8

Terminals

Terminal type	F-M6
Terminal layout	See layout

Performance & Characteristics

Internal Resistance mOhm	
Self Discharge	
Construction Type	Non-Spillable VRLA - Valve Regulated Lead Acid Particularly suitable for cyclic applications Maintenance-free (no topping up)

Design Life - EUROBAT Classification

6-9 years General Purpose

Approvals

Applications

All Purpose, Uninterruptable Power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.

450 cycles according to IEC 60 254-1



Layout



Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813 f 020 8397-1799

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk