



## DATA SHEET

### GF12065Y Sonnenschein Gel Battery

#### Specifications

|                   |     |
|-------------------|-----|
| Nominal Voltage   | 12v |
| Capacity - c20 Ah | 78  |
| Capacity - c10 Ah |     |
| Capacity - c5 Ah  | 65  |

#### Dimensions mm

|                       |      |
|-----------------------|------|
| Length                | 353  |
| Width                 | 175  |
| Height                |      |
| Height over Terminals | 190  |
| Weight Kg             | 26.8 |

#### Terminals

|                 |                                      |
|-----------------|--------------------------------------|
| Terminal type   | A - Standard tapered automotive post |
| Terminal layout | See layout                           |

#### Performance & Characteristics

|                          |  |
|--------------------------|--|
| Internal Resistance mOhm |  |
| Self Discharge           |  |
| Construction Type        | Non-Spillable<br>VRLA - Valve Regulated Lead Acid<br>Particularly suitable for cyclic applications<br>Maintenance-free (no topping up) |

#### Design Life - EUROBAT Classification

6-9 years General Purpose

#### Approvals


#### Applications

All Purpose, Uninterruptable Power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.

450 cycles according to IEC 60 254-1



#### Layout



#### Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

### CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813 f 020 8397-1799

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk