



## DATA SHEET

### GF12090V

### Sonnenschein Gel Battery

#### Specifications

Nominal Voltage	12v
Capacity - c20 Ah	98
Capacity - c10 Ah	
Capacity - c5 Ah	90

#### Dimensions mm

Length	513
Width	189
Height	
Height over Terminals	219
Weight Kg	36.5

#### Terminals

Terminal type	A- Standard tapered automotive post
Terminal Layout	See layout

#### Performance & Characteristics

Internal Resistance mOhm

Self Discharge

Construction Type

Non-Spillable  
VRLA - Valve Regulated Lead Acid  
Particularly suitable for cyclic applications  
Maintenance-free (no topping up)

#### Design Life - EUROBAT Classification

6-9 years General Purpose

#### Approvals


#### Applications

All Purpose, Uninterruptable Power Supply (UPS),  
Electric Power System (EPS), Emergency Backup Power  
supply, Emergency Lighting, Railway Signal, Aircraft  
Signal, Alarm and Security System, Electronic  
Apparatus and Equipment, Communication Power  
Supply, DC Power Supply, Auto Control System.

700 cycles according to IEC 60 254-1



#### Layout



#### Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

### CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813 f 020 8397-1799

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk