



## GS Technical Data Sheet

### GS SMF078 - GS SMF Battery

#### Performance

|                          |      |
|--------------------------|------|
| Voltage                  | 12V  |
| Capacity (20-hour)       | 60Ah |
| Cold Cranking Amps (EN1) | 540A |

#### Dimensions

|        |       |
|--------|-------|
| Length | 242mm |
| Width  | 175mm |
| Height | 190mm |

#### Weights & Measures

|                       |        |
|-----------------------|--------|
| Mean Weight with Acid | 15.1kg |
|-----------------------|--------|



#### Container Features

|                           |    |
|---------------------------|----|
| Case Type                 | L2 |
| Cell Layout               | 1  |
| Hold Down                 | B3 |
| State of Charge Indicator | ✓  |
| Handles                   | ✓  |
| End Venting               | ✓  |

#### Technology

|                         |             |
|-------------------------|-------------|
| Flame Arrestor          | ✓           |
| Technology              | Ca/Ca       |
| Separator               | PE          |
| Recommended Charge Rate | A           |
| Performance Marking     | W4-C2-V2-E1 |

#### Terminal Type

#### Cell Assembly Layout

#### Battery Hold-down

##### T1

Standard DIN Post



Data Sheet generated on 09/06/2020 - E&OE