



DATA SHEET

GF12 25YG

Sonnenschein Gel Battery

Specifications

Nominal Voltage	12
Capacity - c20 Ah	28
Capacity - c10 Ah	
Capacity - c5 Ah	25

Dimensions mm

Length	197
Width	132
Height	
Height over Terminals	180
Weight Kg	11.1

Terminals

Terminal type	M6
Terminal Layout	See layout

Performance & Characteristics

Internal Resistance mOhm

Self Discharge

Construction Type	Non-Spillable VRLA - valve Regulated Lead Acid Particularly suitable for cyclic applications Maintenance-free (no topping up)
-------------------	--

Design Life - EUROBAT Classification

3-5 years General Purpose

Approvals

Applications

All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power Supply, DC Power Supply, Auto Control System.

450 cycles according to IEC 60 254-1



Layout



Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813 f 020 8397-1799

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk