



DATA SHEET

GF12105V

Sonnenschein Gel Battery

Specifications

Nominal Voltage	12v
Capacity - c20 Ah	120
Capacity - c10 Ah	
Capacity - c5 Ah	105

Dimensions mm

Length	345
Width	174
Height	
Height over Terminals	283
Weight Kg	37.5

Terminals

Terminal type	A - Standard tapered automotive post
---------------	--------------------------------------

Terminal Layout

Performance & Characteristics

Internal Resistance mOhm

Self Discharge

Construction Type

Non-Spillable
VRLA - valve Regulated Lead Acid
Particularly suitable for cyclic applications
Maintenance-free (no topping up)

Design Life - EUROBAT Classification

3-5 years General Purpose

Approvals


Applications

All Purpose, Uninterruptable power Supply (UPS),
Electric Power System (EPS), Emergency Backup
Power supply, Emergency Lighting, railway Signal,
Aircraft Signal, Alarm and Security System, Electronic
Apparatus and Equipment, Communication Power
Supply, DC Power Supply, Auto Control System.

700 cycles according to IEC 60254-1



Layout



Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813 f 020 8397-1799

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk