

DATA SHEET NP12-6 Yuasa AGM Battery Specifications Nominal Voltage 6 Capacity - c20 Ah 12 V.12Ah Capacity - c10 Ah 11.1 Capacity - c5 Ah UASA **Dimensions mm** Pb Length 151 SA BATTERY (UK) LTD Width 50 Height **Height over Terminals** 97.5 Weight Kg 2.05 Terminals Layout **Terminal type** Faston 6.35 **Terminal Layout** See Layout Performance & Characteristics Internal Resistance m0hm Self Discharge **Construction Type** Case Material - ABS (UL.94:HB) VRLA - Valve Regulated Lead Acid AGM - Absorbed Glass Matt Maintenance-free (no topping up) Design Life - EUROBAT Classification 3-5 years General Purpose Approvals Underwriters Laboratories (UL) USA Recyclable Applications All Purpose, Uninterruptable power Supply (UPS), Electric Power System (EPS), Emergency Backup Power supply, Emergency Lighting, Railway Signal, Aircraft Signal, Alarm and Security System, Electronic Apparatus and Equipment, Communication Power

CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

Supply, DC Power Supply, Auto Control System.

CPC Battery Services Ltd Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813 f 020 8397-1799

sales@cpcbatteries.co.uk www.cpcbatteries.co.uk