



DATA SHEET

NPW45-12

Yuasa AGM Battery

Specifications

Nominal Voltage	12
Capacity - c20 Ah	8.5
Capacity - c10 Ah	7.42
Capacity - c5 Ah	

Dimensions mm

Length	151
Width	65
Height	94
Height over Terminals	97.5
Weight Kg	2.7

Terminals

Terminal type	FASTON 6.35mm
Terminal Layout	See Layout

Performance & Characteristics

Internal Resistance mOhm

Self Discharge

Construction Type

Case Material - ABS (UL94:HB)
 VRLA - Valve Regulated Lead Acid
 AGM - Absorbed Glass Matt
 Maintenance-free (no topping up)

Design Life - EUROBAT Classification

3-5 years General Purpose

Approvals

Underwriters Laboratories (UL) USA

Applications

Alarm systems, Communication equipment, Control equipment, Emergency lighting, Fire and security systems, Solar and UPS systems

High performance batteries specially designed for applications requiring high rate discharge, supplying up to 50% (NPH), (NPW) more power (Watts) for short durations when compared to conventional NP models.



Layout



Recyclable



CPC Batteries accepts no liability for changes by the manufacturer - Suitability for application remains the responsibility of the end user

CPC Battery Services Ltd

Chancerygate Business Centre, 214 Red Lion Road, Surbiton, Surrey KT6 7RA

t 020 8397-1813 f 020 8397-1799

sales@cpcbatteries.co.uk

www.cpcbatteries.co.uk